

A Quick Guide for the QZ Package

Wei-Chen Chen

Computer Science and Mathematics Division,
Oak Ridge National Laboratory,
Oak Ridge, TN, USA

Contents

Acknowledgement	ii
1. Introduction	1
2. Methods	1
2.1. Generalized Eigenvalues for Pair Matrices	1
2.2. QZ Decomposition for Pair Matrices	1
3. Implementation	2
4. Data Example	3
References	15

Acknowledgement

Wei-Chen Chen was supported in part by the project “Visual Data Exploration and Analysis of Ultra-large Climate Data” funded by U.S. DOE Office of Science under Contract No. DE-AC05-00OR22725.

Warning: This document is written to explain the main functions of **QZ** package (Chen 2013), version 0.1-3. Every effort will be made to ensure future versions are consistent with these instructions, but features in later versions may not be explained in this document.

1. Introduction

This article is to explain the **QZ** package (Chen 2013), and is organized as the following. Section 2 introduces briefly background of generalized eigenvalues problem and QZ decomposition. Section 3 lists the main functions and detail Fortran functions of LAPACK library (Anderson *et al.* 1999).

2. Methods

Some details can be found on wikipedia website at

http://en.wikipedia.org/wiki/Eigendecomposition_of_a_matrix

for generalized eigenvalues, and at

http://en.wikipedia.org/wiki/Schur_decomposition

about QZ decomposition or generalized Schur form. The LAPACK (Anderson *et al.* 1999) also provides functions to solve these problems.

2.1. Generalized Eigenvalues for Pair Matrices

Suppose \mathbf{A} and \mathbf{B} are two $N \times N$ non-symmetric matrices which can be both in real or in complex. The goal is to find right generalized eigen vectors \mathbf{v} such that $\mathbf{A}\mathbf{v} = \lambda\mathbf{B}\mathbf{v}$, or left generalized eigen vectors \mathbf{u} such that $\mathbf{u}^H\mathbf{A} = \lambda\mathbf{u}^H\mathbf{B}$ where \mathbf{u}^H is the conjugate-transpose of \mathbf{u} . Also, λ is called generalized eigenvalues of \mathbf{A} and \mathbf{B} which obeys $\det(\mathbf{A} - \lambda\mathbf{B}) = 0$. Note that λ , \mathbf{u} , and \mathbf{v} may be complex even \mathbf{A} and \mathbf{B} are in real.

Suppose \mathbf{B} is an identity matrix \mathbf{I} , then the problem reduces to traditional eigenvalue problem. i.e. This is a special case.

2.2. QZ Decomposition for Pair Matrices

Suppose \mathbf{A} and \mathbf{B} are two $N \times N$ non-symmetric matrices which can be both in real or in complex. The QZ decomposition factorizes both matrices as

- $\mathbf{A} = \mathbf{Q}\mathbf{S}\mathbf{Z}^\top$ and $\mathbf{B} = \mathbf{Q}\mathbf{T}\mathbf{Z}^\top$ if \mathbf{A} and \mathbf{B} are real, or
- $\mathbf{A} = \mathbf{Q}\mathbf{S}\mathbf{Z}^H$ and $\mathbf{B} = \mathbf{Q}\mathbf{T}\mathbf{Z}^H$ if \mathbf{A} and \mathbf{B} are complex

where \mathbf{Q} and \mathbf{Z} are unitary and \mathbf{S} and \mathbf{T} are upper triangular. The unitary means $\mathbf{X}\mathbf{X}^H = \mathbf{I}$ if \mathbf{X} is complex or $\mathbf{X}\mathbf{X}^\top = \mathbf{I}$ if \mathbf{X} is real where \mathbf{I} is the identity matrix.

The QZ decomposition is also called generalized Schur decomposition where \mathbf{S} and \mathbf{T} are the Schur form of \mathbf{A} and \mathbf{B} . The generalized eigenvalues λ that solve the generalized eigenvalue problem $\mathbf{A}\mathbf{x} = \lambda\mathbf{B}\mathbf{x}$ where \mathbf{x} is an unknown nonzero vector and $\lambda_i = \mathbf{S}_{ii}/\mathbf{T}_{ii}$.

Suppose \mathbf{B} is an identity matrix \mathbf{I} , then the problem reduces to find \mathbf{Q} such that $\mathbf{A} = \mathbf{Q}\mathbf{S}\mathbf{Q}^{-1}$ for real \mathbf{A} or $\mathbf{A} = \mathbf{Q}\mathbf{S}\mathbf{Q}^H$ for complex \mathbf{A} . i.e. This is a special case.

3. Implementation

Two main functions are `geigen()` for generalized eigenvalues, and `qz()` for QZ decomposition with reordering capability. Both functions are able to deal a single matrix \mathbf{A} or a paired matrices (\mathbf{A}, \mathbf{B}) in both complex and real systems. Both functions are wrapper functions for several lower level R functions `qz.*()` which are also wrapper functions via `.Call()` for C and Fortran functions to LAPACK library version 3.4.2.

LAPACK library is incorporated in **QZ** including complex*16 and double precision for complex and real systems respectively. **QZ** has functions of LAPACK and BLAS (Blackford *et al.* 2002) independently to the R's LAPACK and BLAS libraries since some functions are not available. Table 1 provides a detail lists for the `qz.*()` functions.

Table 1: **QZ** functions

Function	Wrapper	Main Input	System	Purpose
<code>geigen()</code>	<code>qz.zgeev</code>	\mathbf{A}	Complex	Generalized eigenvalues
	<code>qz.dgeev</code>	\mathbf{A}	Real	
<code>qz()</code>	<code>qz.zgees</code>	\mathbf{A}	Complex	QZ decomposition
	<code>qz.dgees</code>	\mathbf{A}	Real	
	<code>qz.ztrsen</code> <code>qz.dtrsen</code>	\mathbf{T}, \mathbf{Q} \mathbf{T}, \mathbf{Q}	Complex Real	Reordering
<code>geigen()</code>	<code>qz.zggev</code>	(\mathbf{A}, \mathbf{B})	Complex	Generalized eigenvalues
	<code>qz.dggev</code>	(\mathbf{A}, \mathbf{B})	Real	
<code>qz()</code>	<code>qz.zgges</code>	(\mathbf{A}, \mathbf{B})	Complex	QZ decomposition
	<code>qz.dgges</code>	(\mathbf{A}, \mathbf{B})	Real	
	<code>qz.ztgsgen</code> <code>qz.dtgsgen</code>	$(\mathbf{S}, \mathbf{T}), \mathbf{Q}, \mathbf{Z}$ $(\mathbf{S}, \mathbf{T}), \mathbf{Q}, \mathbf{Z}$	Complex Real	Reordering

An extra MATLAB-like function `ordqz()` is also available to reordering generalized eigenvalues and QZ decomposition results. The function which is the combinations of `qz()` and `qz.ztrsen()/qz.dtrsen()` for specified ordering keywords in Table 2. Note that `select`

Table 2: The `ordez()` keyword for reording.

keyword	Purpose
<code>lhp</code>	Left-half ($\text{real}(\mathbf{E}) < 0$)
<code>rhp</code>	Right-half ($\text{real}(\mathbf{E}) > 0$)
<code>udi</code>	Interior of unit disk ($\text{abs}(\mathbf{E}) < 1$)
<code>udo</code>	Exterior of unit disk ($\text{abs}(\mathbf{E}) > 1$)
<code>ref</code>	Real eigenvalues first (top-left conner)
<code>cef</code>	Complex eigenvalues first (top-left conner)

argument of `qz()` allows users to specify any order to group and reorder the decompositions.

4. Data Example

There are four demos for the **QZ** package which are listed in Table 3

Table 3: The demos of **QZ** package.

demo	Purpose
ex1_geigen	<code>geigen()</code> for double/complex single/paired matrices
ex2_qz	<code>qz()</code> for double/complex single/paired matrices
ex3_ordqz	<code>ordqz()</code> and arbitrary reordering
ex4_fda_geigen	generalized eigen analysis of fda package (Ramsay <i>et al.</i> 2013)

There are also several datasets for **QZ** package to verify results which are listed in Table 4.

Table 4: The datasets of **QZ** package.

data	Source
exAB1	http://www.nag.com/lapack-ex/node124.html
exAB2	http://www.nag.com/lapack-ex/node119.html
exAB3	http://www.nag.com/numeric/fl/nagdoc_f123/xhtml/F08/f08yuf.xml
exAB4	http://www.nag.com/numeric/fl/nagdoc_f123/xhtml/F08/f08yuf.xml
exA1	http://www.nag.com/lapack-ex/node94.html
exA2	http://www.nag.com/lapack-ex/node89.html
exA3	http://www.nag.com/numeric/fl/nagdoc_f123/xhtml/F08/f08quf.xml
exA4	http://www.nag.com/numeric/fl/nagdoc_f122/xhtml/F08/f08quf.xml

These demos can be obtained in R by the following.

QZ demo ex1_geigen

```
> demo(ex1_geigen, 'QZ')

      demo(ex1_geigen)
      ---- ~~~~~

Type <Return> to start :

> library(QZ, quiet = TRUE)

> ### http://www.nag.com/lapack-ex/node122.html
> (ret <- geigen(exAB1$A, exAB1$B))
ALPHA:
[1] 19.03-57.10i 11.88-29.70i 10.96- 3.65i 21.87-27.34i

BETA:
```

```

[1] 6.344+0i 5.941+0i 3.654+0i 5.468+0i

U:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.0358-0.1155i 0.0725-0.3001i 0.1650-0.0068i 0.01727-0.02542i
[2,] 0.2152+0.2357i -0.2139+0.7641i 0.0999-0.8330i -0.01045-0.09180i
[3,] -0.2425+0.4271i 0.7520-0.2317i -0.9374-0.0626i -0.17518-0.82482i
[4,] 0.5658-0.4342i -0.1782-0.8218i -0.0529+0.1385i -0.84361-0.01589i

V:
      [,1]      [,2]      [,3]
      [,4]
[1,] -0.8238-0.1762i 0.63974+0.360259i 0.9775+0.0225i
      -0.90623+0.093766i
[2,] -0.1530+0.0707i 0.00416-0.000547i 0.1591-0.1137i
      -0.00743+0.006875i
[3,] -0.0707-0.1530i 0.04021+0.022645i 0.1209-0.1537i
      0.03021-0.003126i
[4,] 0.1530-0.0707i -0.02264+0.040212i 0.1537+0.1209i
      -0.01459-0.140970i

> ### http://www.nag.com/lapack-ex/node117.html
> (ret <- geigen(exAB2$A, exAB2$B))
ALPHA:
[1] 3.801+0.000i 3.030+4.040i 1.563-2.084i 4.000+0.000i

BETA:
[1] 1.900 1.010 0.521 1.000

U:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.53333+0i 0.2171-0.1284i 0.2171+0.1284i -7.276e-17+0i
[2,] -0.06667+0i 0.1744-0.1851i 0.1744+0.1851i -1.000e+00+0i
[3,] -1.00000+0i -0.7928+0.2072i -0.7928-0.2072i 1.000e+00+0i
[4,] 0.60000+0i 0.3912+0.0911i 0.3912-0.0911i -3.695e-16+0i

V:
      [,1]      [,2]      [,3]      [,4]
[1,] 1.000000+0i -0.4398-0.5602i -0.4398+0.5602i -1.000000+0i
[2,] 0.005714+0i -0.0880-0.1120i -0.0880+0.1120i -0.011111+0i
[3,] 0.062857+0i -0.1424+0.0031i -0.1424-0.0031i 0.033333+0i
[4,] 0.062857+0i -0.1424+0.0031i -0.1424-0.0031i -0.15556+0i

> ### http://www.nag.com/lapack-ex/node92.html
> (ret <- geigen(exA1$A))
W:
[1] -6.000-7.000i -5.000+2.006i 7.998-0.996i 3.002-4.000i

U:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.8357+0.0000i -0.3510+0.1013i -0.1689+0.2595i 0.1099-0.2007i
[2,] -0.0794+0.3372i -0.4035+0.4540i 0.6762+0.0000i 0.0336+0.2312i
[3,] 0.0917+0.3097i 0.6239+0.0000i 0.3032+0.5642i 0.0944-0.3947i

```

```

[4,] 0.0456-0.2741i -0.0816-0.3190i 0.1328+0.1376i 0.8534+0.0000i
V:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.8457+0.0000i -0.3865+0.1732i -0.1730+0.2669i -0.0356-0.1782i
[2,] -0.0177+0.3036i -0.3539+0.4529i 0.6924+0.0000i 0.1264+0.2666i
[3,] 0.0875+0.3115i 0.6124+0.0000i 0.3324+0.4960i 0.0129-0.2966i
[4,] -0.0561-0.2906i -0.0859-0.3284i 0.2504-0.0147i 0.8898+0.0000i

> ### http://www.nag.com/lapack-ex/node87.html
> (ret <- geigen(exA2$A))
W:
[1] 0.7995+0.0000i -0.0994+0.4008i -0.0994-0.4008i -0.1007+0.0000i
U:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.62447+0i 0.5330+0.0000i 0.5330+0.0000i 0.6641+0i
[2,] -0.59949+0i -0.2666+0.4041i -0.2666-0.4041i -0.1068+0i
[3,] 0.49992+0i 0.3455+0.3153i 0.3455-0.3153i 0.7293+0i
[4,] -0.02709+0i -0.2541-0.4451i -0.2541+0.4451i 0.1249+0i
V:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.65509+0i -0.1933+0.2546i -0.1933-0.2546i 0.1253+0i
[2,] -0.52363+0i 0.2519-0.5224i 0.2519+0.5224i 0.3320+0i
[3,] 0.53622+0i 0.0972-0.3084i 0.0972+0.3084i 0.5938+0i
[4,] -0.09561+0i 0.6760+0.0000i 0.6760+0.0000i 0.7221+0i

```

QZ demo ex2_qz

```

> demo(ex2_qz, 'QZ')

      demo(ex2_qz)
      ---- ~~~~~

Type <Return> to start :

> library(QZ, quiet = TRUE)

> ### http://www.nag.com/lapack-ex/node124.html
> (ret <- qz(exAB1$A, exAB1$B))
ALPHA:
[1] 19.03-57.10i 11.88-29.70i 10.96- 3.65i 21.87-27.34i

BETA:
[1] 6.344+0i 5.941+0i 3.654+0i 5.468+0i
S:
      [,1]      [,2]      [,3]      [,4]
[1,] 19.03-57.1i 53.59-89.82i -81.31-63.23i 106.66-44.79i
[2,] 0.00+ 0.0i 11.88-29.70i 3.56+27.63i -0.67-16.42i
[3,] 0.00+ 0.0i 0.00+ 0.00i 10.96- 3.65i -25.02- 8.20i
[4,] 0.00+ 0.0i 0.00+ 0.00i 0.00+ 0.00i 21.87-27.34i

```

```

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 6.344+0i 3.399+0.712i -0.515-2.382i 6.582+2.430i
[2,] 0.000+0i 5.941+0.000i -2.448-0.343i 5.739-0.702i
[3,] 0.000+0i 0.000+0.000i 3.654+0.000i -1.410-3.933i
[4,] 0.000+0i 0.000+0.000i 0.000+0.000i 5.468+0.000i

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.3347+0.7387i 0.2872-0.4789i 0.1725+0.0093i 0.01443-0.02124i
[2,] -0.1277+0.2493i -0.0282+0.4999i 0.1541-0.8008i -0.00873-0.07670i
[3,] -0.3557+0.0396i -0.4615-0.0822i -0.3939+0.0258i -0.14637-0.68917i
[4,] -0.0126-0.3682i 0.1508-0.4417i 0.1517-0.3555i -0.70486-0.01328i

Z:
      [,1]      [,2]      [,3]
[1,] -0.9240-0.1977i 0.2460+0.2090i -0.00543+0.05421i
      0.000e+00+0.000e+00i
[2,] -0.1716+0.0793i -0.5943+0.0905i 0.74673-0.21271i
      -1.092e-16-3.690e-16i
[3,] -0.0793-0.1716i 0.0943-0.5082i 0.01020-0.44383i
      7.034e-01-7.277e-02i
[4,] 0.1716-0.0793i 0.5082+0.0943i 0.44383+0.01020i
      -7.277e-02-7.034e-01i

> ### http://www.nag.com/lapack-ex/node119.html
> (ret <- qz(exAB2$A, exAB2$B))
ALPHA:
[1] 3.801+0.000i 3.030+4.040i 1.563-2.084i 4.000+0.000i

BETA:
[1] 1.900 1.010 0.521 1.000

S:
      [,1]      [,2]      [,3]      [,4]
[1,] 3.801 31.326 -61.485 -66.836
[2,] 0.000 3.351 7.074 6.692
[3,] 0.000 -1.192 1.410 4.379
[4,] 0.000 0.000 0.000 4.000

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 1.9 -1.078 -5.6252 -9.987
[2,] 0.0 1.176 0.0000 1.751
[3,] 0.0 0.000 0.4474 1.090
[4,] 0.0 0.000 0.0000 1.000

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.4642 0.81159 0.3547 -5.145e-17
[2,] 0.5002 -0.06975 -0.4950 -7.071e-01
[3,] 0.5002 -0.06975 -0.4950 7.071e-01

```



```

[4,] 0.5331 -0.57585 0.6198 -2.613e-16

Z:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.996056 0.08183 -0.03428 0.000e+00
[2,] 0.005692 -0.44454 -0.89574 5.145e-17
[3,] 0.062609 -0.63075 0.31343 7.071e-01
[4,] 0.062609 -0.63075 0.31343 -7.071e-01

> ### http://www.nag.com/lapack-ex/node94.html
> (ret <- qz(exA1$A))
W:
[1] -6.000-7.000i -5.000+2.006i 7.998-0.996i 3.002-4.000i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] -6-7i 0.1618+0.4896i 0.4761-0.1946i 0.8633-0.3014i
[2,] 0+0i -5.0000+2.0060i 0.6907+0.2115i 0.2281+0.1328i
[3,] 0+0i 0.0000+0.0000i 7.9982-0.9964i -1.0155+0.3626i
[4,] 0+0i 0.0000+0.0000i 0.0000+0.0000i 3.0023-3.9998i

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.5312-0.6581i -0.0799-0.3774i -0.0935-0.2736i 0.1869-0.1321i
[2,] 0.2474-0.1769i -0.4108-0.4021i -0.4015+0.6010i -0.0713+0.2225i
[3,] 0.1874-0.2637i -0.0937+0.6241i -0.5752-0.0389i 0.2581-0.3132i
[4,] -0.1909+0.2262i 0.3457-0.0537i -0.1537+0.1951i 0.7668+0.3747i

> ### http://www.nag.com/lapack-ex/node89.html
> (ret <- qz(exA2$A))
W:
[1] 0.7995+0.0000i -0.0994+0.4008i -0.0994-0.4008i -0.1007+0.0000i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.7995 0.006037 -0.11445 -0.03357
[2,] 0.0000 -0.099412 -0.64834 -0.20258
[3,] 0.0000 0.247764 -0.09941 -0.34742
[4,] 0.0000 0.000000 0.00000 -0.10066

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.65509 -0.3450 -0.1037 0.6641
[2,] -0.52363 0.6141 0.5807 -0.1068
[3,] 0.53622 0.2935 0.3073 0.7293
[4,] -0.09561 0.6463 -0.7467 0.1249

```

QZ demo ex3_ordqz

```

> demo(ex3_ordqz, 'QZ')

demo(ex3_ordqz)

```

```

----- ~~~~~
Type <Return> to start :

> # Reordering eigenvalues
> library(QZ, quiet = TRUE)

> select <- c(TRUE, FALSE, FALSE, TRUE)

> (ret <- qz(exAB1$A, exAB1$B, select = select))
ALPHA:
[1] 19.033-57.099i 17.897-22.371i 18.175-45.437i 8.757- 2.919i

BETA:
[1] 6.344+0i 4.474+0i 9.087+0i 2.919+0i

S:
      [,1]      [,2]      [,3]      [,4]
[1,] 19.03-57.1i 0.07-93.12i -128.250- 6.366i -98.392+ 9.509i
[2,] 0.00+ 0.0i 17.90-22.37i 0.581- 4.575i 6.972+17.755i
[3,] 0.00+ 0.0i 0.00+ 0.00i 18.175-45.437i -19.992- 6.063i
[4,] 0.00+ 0.0i 0.00+ 0.00i 0.000+ 0.000i 8.757- 2.919i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 6.344+0i 1.427-1.821i -4.137-6.323i -1.783-1.262i
[2,] 0.000+0i 4.474+0.000i -0.003-3.720i -2.992-0.076i
[3,] 0.000+0i 0.000+0.000i 9.087+0.000i -0.777-1.003i
[4,] 0.000+0i 0.000+0.000i 0.000+0.000i 2.919+0.000i

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.3347+0.7387i 0.0511-0.3524i -0.2997+0.3302i 0.08899-0.09359i
[2,] -0.1277+0.2493i 0.3749+0.5365i 0.2504+0.0137i -0.39709-0.52213i
[3,] -0.3557+0.0396i -0.4717+0.2407i 0.0591+0.2199i -0.56045+0.47485i
[4,] -0.0126-0.3682i 0.4020-0.0522i 0.1201+0.8198i 0.04567+0.10657i

Z:
      [,1]      [,2]      [,3]
      [,4]
[1,] -0.9240-0.1977i 0.2234+0.1906i -0.08922-0.09991i
      0.0338+0.04268i
[2,] -0.1716+0.0793i -0.5288+0.0772i 0.27684-0.00803i
      0.3880-0.67191i
[3,] -0.0793-0.1716i -0.1722-0.6151i -0.57435-0.20679i
      -0.2753-0.32832i
[4,] 0.1716-0.0793i 0.3215+0.3418i -0.58658+0.43433i
      0.3229-0.32726i

> ### http://www.nag.com/lapack-ex/node119.html
> select <- c(TRUE, FALSE, FALSE, TRUE)

> (ret <- qz(exAB2$A, exAB2$B, select = select))

```

```

ALPHA:
[1] 3.801+0.000i 9.203+0.000i 0.857+1.143i 0.857-1.143i

BETA:
[1] 1.9005 2.3008 0.2857 0.2857

S:
      [,1]      [,2]      [,3]      [,4]
[1,] 3.801 -69.451 50.3135 -43.288
[2,] 0.000  9.203 -0.2001  5.988
[3,] 0.000  0.000  1.4279  4.445
[4,] 0.000  0.000  0.9019 -1.196

T:
      [,1]      [,2]      [,3]      [,4]
[1,]  1.9 -10.228 0.8658 -5.2134
[2,]  0.0  2.301 0.7915  0.4262
[3,]  0.0  0.000 0.8101  0.0000
[4,]  0.0  0.000 0.0000 -0.2823

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.4642  0.78862  0.29148 -0.2786
[2,] 0.5002 -0.59864  0.56379 -0.2713
[3,] 0.5002  0.01541 -0.01074  0.8657
[4,] 0.5331 -0.13952 -0.77270 -0.3151

Z:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.996056 -0.00140  0.08868 -0.002602
[2,] 0.005692 -0.04037 -0.09376 -0.994760
[3,] 0.062609  0.71938 -0.69084  0.036273
[4,] 0.062609 -0.69344 -0.71140  0.095554

> (ret <- ordqz(exAB2$A, exAB2$B, keyword = "ref"))
ALPHA:
[1] 3.801+0.000i 9.203+0.000i 0.857+1.143i 0.857-1.143i

BETA:
[1] 1.9005 2.3008 0.2857 0.2857

S:
      [,1]      [,2]      [,3]      [,4]
[1,] 3.801 -69.451 50.3135 -43.288
[2,] 0.000  9.203 -0.2001  5.988
[3,] 0.000  0.000  1.4279  4.445
[4,] 0.000  0.000  0.9019 -1.196

T:
      [,1]      [,2]      [,3]      [,4]
[1,]  1.9 -10.228 0.8658 -5.2134
[2,]  0.0  2.301 0.7915  0.4262
[3,]  0.0  0.000 0.8101  0.0000

```

```

[4,] 0.0 0.000 0.0000 -0.2823

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.4642  0.78862  0.29148 -0.2786
[2,] 0.5002 -0.59864  0.56379 -0.2713
[3,] 0.5002  0.01541 -0.01074  0.8657
[4,] 0.5331 -0.13952 -0.77270 -0.3151

Z:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.996056 -0.00140  0.08868 -0.002602
[2,] 0.005692 -0.04037 -0.09376 -0.994760
[3,] 0.062609  0.71938 -0.69084  0.036273
[4,] 0.062609 -0.69344 -0.71140  0.095554

> (ret <- ordqz(exAB2$A, exAB2$B, keyword = "cef"))
ALPHA:
[1] 0.8571+1.143i 0.8571-1.143i 0.6172+0.000i 4.0000+0.000i

BETA:
[1] 0.2857 0.2857 0.3086 1.0000

S:
      [,1]      [,2]      [,3]      [,4]
[1,] -38.566  41.488  37.2809  65.427
[2,]  6.827  -5.244 -12.9545 -15.482
[3,]  0.000  0.000  0.6172  3.252
[4,]  0.000  0.000  0.0000  4.000

T:
      [,1]      [,2]      [,3]      [,4]
[1,] -3.368  0.0000  4.9228  9.696
[2,]  0.000  0.9621 -1.1839 -2.988
[3,]  0.000  0.0000  0.3086  1.027
[4,]  0.000  0.0000  0.0000  1.000

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.5521 -0.67876  0.4842 -5.145e-17
[2,] -0.5106  0.06994 -0.4842 -7.071e-01
[3,] -0.5106  0.06994 -0.4842  7.071e-01
[4,] -0.4169  0.72767  0.5447 -2.613e-16

Z:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.8775  0.43756  1.961e-01  0.000e+00
[2,] 0.1755  0.08751 -9.806e-01  5.145e-17
[3,] -0.3155  0.63281 -2.387e-15  7.071e-01
[4,] -0.3155  0.63281 -2.498e-15 -7.071e-01

> select <- c(TRUE, FALSE, FALSE, TRUE)

```

```

> (ret <- qz(exA1$A, select = select))
W:
[1] -6.000-7.000i  3.002-4.000i  -5.000+2.006i  7.998-0.996i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] -6-7i  0.3254-0.8854i  0.5349-0.0829i  0.0083+0.4285i
[2,]  0+0i  3.0023-3.9998i  0.1669+0.2948i  -0.2477-1.0389i
[3,]  0+0i  0.0000+0.0000i  -5.0000+2.0060i  -0.5188-0.4792i
[4,]  0+0i  0.0000+0.0000i  0.0000+0.0000i  7.9982-0.9964i

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.5312-0.6581i  -0.0184-0.2122i  -0.3775+0.0311i  0.3003+0.0754i
[2,]  0.2474-0.1769i  0.2150+0.2457i  -0.4610+0.3622i  -0.2198-0.6395i
[3,]  0.1874-0.2637i  -0.0469-0.2699i  0.6166+0.1728i  0.4350-0.4701i
[4,] -0.1909+0.2262i  0.8352-0.2747i  -0.0033-0.3207i  0.0869-0.1703i

> ### http://www.nag.com/lapack-ex/node89.html
> select <- c(TRUE, FALSE, FALSE, TRUE)

> (ret <- qz(exA2$A, select = select))
W:
[1]  0.7995+0.0000i  -0.1007+0.0000i  -0.0994+0.4008i  -0.0994-0.4008i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.7995  -0.005914  -0.07508  -0.09268
[2,] 0.0000  -0.100657  0.39367   0.35692
[3,] 0.0000  0.000000  -0.09941  -0.51282
[4,] 0.0000  0.000000  0.31324  -0.09941

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.65509  -0.1210  -0.50323  0.55043
[2,] -0.52363  -0.3286  0.78570  0.02287
[3,]  0.53622  -0.5974  0.09038  0.58945
[4,] -0.09561  -0.7215  -0.34825  -0.59081

> (ret <- ordqz(exA2$A, keyword = "lhp"))
W:
[1] -0.0994+0.4008i  -0.0994-0.4008i  -0.1007+0.0000i  0.7995+0.0000i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.09941  0.24919  0.3491  0.089393
[2,] -0.64462  -0.09941  0.2049  0.090443
[3,]  0.00000  0.00000  -0.1007  0.009467
[4,]  0.00000  0.00000  0.0000  0.799482

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.1733  -0.3607  -0.6707  -0.62447

```

```

[2,] 0.5173 0.6024 0.1005 -0.59949
[3,] 0.3629 0.3067 -0.7241 0.49992
[4,] -0.7554 0.6426 -0.1252 -0.02709

> (ret <- ordqz(exA2$A, keyword = "rhp"))
W:
[1] 0.7995+0.0000i -0.0994+0.4008i -0.0994-0.4008i -0.1007+0.0000i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.7995 0.006037 -0.11445 -0.03357
[2,] 0.0000 -0.099412 -0.64834 -0.20258
[3,] 0.0000 0.247764 -0.09941 -0.34742
[4,] 0.0000 0.000000 0.00000 -0.10066

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.65509 -0.3450 -0.1037 0.6641
[2,] -0.52363 0.6141 0.5807 -0.1068
[3,] 0.53622 0.2935 0.3073 0.7293
[4,] -0.09561 0.6463 -0.7467 0.1249

> (ret <- ordqz(exA2$A, keyword = "ref"))
W:
[1] 0.7995+0.0000i -0.1007+0.0000i -0.0994+0.4008i -0.0994-0.4008i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] 0.7995 -0.005914 -0.07508 -0.09268
[2,] 0.0000 -0.100657 0.39367 0.35692
[3,] 0.0000 0.000000 -0.09941 -0.51282
[4,] 0.0000 0.000000 0.31324 -0.09941

Q:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.65509 -0.1210 -0.50323 0.55043
[2,] -0.52363 -0.3286 0.78570 0.02287
[3,] 0.53622 -0.5974 0.09038 0.58945
[4,] -0.09561 -0.7215 -0.34825 -0.59081

> (ret <- ordqz(exA2$A, keyword = "cef"))
W:
[1] -0.0994+0.4008i -0.0994-0.4008i 0.7995+0.0000i -0.1007+0.0000i

T:
      [,1]      [,2]      [,3]      [,4]
[1,] -0.09941 0.24919 0.09306 -0.348147
[2,] -0.64462 -0.09941 0.09259 -0.203889
[3,] 0.00000 0.00000 0.79948 0.009467
[4,] 0.00000 0.00000 0.00000 -0.100657

Q:
      [,1]      [,2]      [,3]      [,4]

```

```
[1,] -0.1733 -0.3607 -0.6315  0.6641
[2,]  0.5173  0.6024 -0.5984 -0.1068
[3,]  0.3629  0.3067  0.4923  0.7293
[4,] -0.7554  0.6426 -0.0284  0.1249
```

QZ demo ex4_fda_geigen

```
> demo(ex4_fda_geigen, 'QZ')

      demo(ex4_fda_geigen)
      ---- ~~~~~

Type <Return> to start :

> library(QZ, quiet = TRUE)

> ### Generate Data
> set.seed(123)

> X <- matrix(rnorm(500), nrow = 25)

> X <- t(X) %*% X

> A <- X[1:8, 9:20]

> B <- X[1:8, 1:8]

> C <- X[9:20, 9:20]

> ### Perform generalized eigenanalysis
> ret.qz <- fda.geigen(A, B, C)

> ret.fda <- fda::geigen(A, B, C)

> ### Verify
> round(abs(ret.qz$values - ret.fda$values))
[1] 0 0 0 0 0 0 0 0

> round(abs(ret.qz$Lmat - ret.fda$Lmat))
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8]
[1,]    0    0    0    0    0    0    0    0
[2,]    0    0    0    0    0    0    0    0
[3,]    0    0    0    0    0    0    0    0
[4,]    0    0    0    0    0    0    0    0
[5,]    0    0    0    0    0    0    0    0
[6,]    0    0    0    0    0    0    0    0
[7,]    0    0    0    0    0    0    0    0
[8,]    0    0    0    0    0    0    0    0

> round(abs(ret.qz$Mmat - ret.fda$Mmat))
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8]
[1,]    0    0    0    0    0    0    0    0
```


References

- Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J, Du Croz J, Greenbaum A, Hammarling S, McKenney A, Sorensen D (1999). *LAPACK Users' Guide*. Third edition. Society for Industrial and Applied Mathematics, Philadelphia, PA. ISBN 0-89871-447-8 (paperback).
- Blackford L, Demmel J, Dongarra J, Duff I, Hammarling S, Henry G, Heroux M, Kaufman L, Lumsdaine A, Petitet A, Pozo R, Remington K, Whaley R (2002). "An Updated Set of Basic Linear Algebra Subprograms (BLAS)." *ACM Trans. Math. Soft.*, **28**, 135–151. URL <http://www.netlib.org/blas/>.
- Chen WC (2013). "QZ: Generalized Eigenvalues and QZ Decomposition." R Package, URL <http://cran.r-project.org/package=QZ>.
- Ramsay J, Wickham H, Graves S, Hooker G (2013). "fda: Functional Data Analysis." R Package, URL <http://cran.r-project.org/package=fda>.